

1 Firmware Description

1.1 INSTEON Commands Supported

1.1.1 Standard length common INSTEON commands:

All direct commands will be ignored if the sender's ID is not in the I2CS device's database with the exceptions below. The SwitchLinc On-Off Dual-Band will reply with a NAK and 0xFF in cmd2 to indicate that the ID is not in the database.

1.1.2 Standard length SwitchLinc On-Off Dual-Band INSTEON commands: Assign to ALL-Link Group Command

Description: Sent when holding down the SET Button for 3 seconds on the device. Blinks the LED green for 4 minutes or until linked to another device.

Example (Hex): AA BB CC 02 2A XX CF 01 01 (where AA.BB.CC is the Device's ID)

SD Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Notes
Assign to ALL-Link Group	From Device	Device's ID	0x02, 0x2A, 0xFF (firmware revision)	Broadcast	0x01	0x01	Sent when holding down SET Button for 3 seconds. Group number for SwitchLinc On-Off Dual-Band is 0x01

Delete from ALL-Link Group Command

Description: Sent when holding down the SET Button for 3 seconds on the device, then pressing and holding the set button for 3 seconds. Blinks the LED red for 4 minutes or until unlinked from another device.

Example (Hex): AA BB CC 02 2A XX CF 02 01 (where AA.BB.CC is the Device's ID)

Delete from ALL-Link Group	From Device	Device's ID	0x02, 0x2A, 0xFF (firmware revision)	Broadcast	0x02	0x01	Group number for SwitchLinc On-Off Dual-Band is 0x01
----------------------------	-------------	-------------	--------------------------------------	-----------	------	------	--

Ping Command

Description: Same as holding down the SET Button for 3 seconds on the device, then pressing and holding the set button for 3 seconds. Blinks the LED red for 4 minutes or until unlinked from another device.

Example (Hex): AA BB CC DD EE FF 0F 0A 01 (where AA.BB.CC is the Device's ID, DD.EE.FF is the Sender's Id)

Ping	To device	Sender's ID	Device's ID	Direct	0x0F	0x00 -> 0xFF (Don't Care Value)	
	Response	Device's ID	Sender's ID	Ack	0x0F	Same as sent	

ID Request Command

Description: Same as holding down the SET Button for 3 seconds on the device, then pressing and holding the set button for 3 seconds. Blinks the LED red for 4 minutes or until unlinked from another device.

Example (Hex): AA BB CC DD EE FF 0F 0A 01 (where AA.BB.CC is the Device's ID, DD.EE.FF is the Sender's Id)

ID Request	To device	Sender's ID	Device's ID	Direct	0x10	0x00 -> 0xFF (Don't Care Value)	
	Response	Device's ID	Sender's ID	Ack	0x10	Same as sent	
	Sent from Device	Device's ID	0x02 0x2A 0xXX (firmware revision)	Broadcast	0x01	0x00	Same as holding down SET Button for 3 seconds, but device not in linking mode

SD Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Notes
Status Request	To device	Sender's ID	Device's ID	Direct	0x19	0x00	
	Response	Device's ID	Sender's ID	Ack	Database Delta	Switch On level	

Success Report Broadcast

Description: Sent at the end of a group broadcast

Example (Hex): AA BB CC 11 03 01 CF 06 01 (where AA.BB.CC is the Device's ID, cleanup of cmd1 = 0x11, group = 0x01, 1 out of 3 devices failed to cleanup correctly)

SD Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Notes
Broadcast cleanup	From device	Device's ID	Hi byte = cmd1 being Cleaned up Med byte = Number of devices to be cleaned up Lo byte = Group Number	Group Broadcast	0x06	0x00 -> 0xFF (Number of Failed Cleanups)	

Standard length SwitchLinc On-Off Dual-Band INSTEON commands:

SD Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Notes
Light ON	To device	Sender's ID	Device's ID	Direct	0x11	0x00 -> 0xFF (on level)	Go to On-Level
	Response	Device's ID	Sender's ID	Ack	0x11	Same as sent	

Light ON Fast	To device	Sender's ID	Device's ID	Direct	0x12	0x00 -> 0xFF (on level)	Go to On-Level instantly
	Response	Device's ID	Sender's ID	Ack	0x12	Same as sent	

Light OFF	To device	Sender's ID	Device's ID	Direct	0x13	0x00 -> 0xFF (on level)	Go to Off at saved Ramp Rate
	Response	Device's ID	Sender's ID	Ack	0x13	Same as sent	

Light OFF Fast	To device	Sender's ID	Device's ID	Direct	0x14	0x00 -> 0xFF (Don't Care Value)	Go to Off instantly
	Response	Device's ID	Sender's ID	Ack	0x14	Same as sent	

SD Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Notes
Read Operating Flags	To device	Sender's ID	Device's ID	Direct	0x1F	Operating Flags Command	See Read Operating Flags Table
	Response	Device's ID	Sender's ID	Ack	0x1F	Same as sent	

Read Operating Flags Table	
0	bit 0 = Plock bit 1 = LED on TX bit 2 = Resume Dim bit bit 2 = N/A bit 4 = LED OFF bit 5 = LoadSense
1	Data Base Delta flag....gets incremented with any change in the Database

SD Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Notes
Instant On/Off	To device	Sender's ID	Device's ID	Direct	0x21	0x00 -> 0xFF (on level)	Uses instant Ramp Rate
	Response	Device's ID	Sender's ID	Ack	0x21	Same as sent	

Remote Tap of Set Button	To device	Sender's ID	Device's ID	Direct	0x25	0x00 = Set On Level, 0x02 = Set RR	Load must first be set to corresponding On Level (0x11)
	Response	Device's ID	Sender's ID	Ack	0x25	Same as sent	

RR On	To device	Sender's ID	Device's ID	Direct	0x2E	On level = $16 * On + 0F$ RR = $2 * RR + 1$	
	Response	Device's ID	Sender's ID	Ack	0x2E	Same as sent	

RR Off	To device	Sender's ID	Device's ID	Direct	0x2F	On level = 00 RR = $2 * RR + 1$	
	Response	Device's ID	Sender's ID	Ack	0x2F	Same as sent	

Beep	To device	Sender's ID	Device's ID	Direct	0x30	0x00 -> 0xFF (Don't care value)	Beeps for standard duration (same as Set Button Pressed)
	Response	Device's ID	Sender's ID	Ack	0x30	Same as sent	

1.1.3 Extended length SwitchLinc On-Off Dual-Band INSTEON commands:

Remote Enter Linking Mode Command

Description: Same as holding down the SET Button for 3 seconds on the device. Blinks the LED red for 4 minutes or until unlinked from another device.

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Data 1 (1 byte)	Data 2 (1 byte)
Enter Linking Mode	To device	Sender's ID	Device's ID	Extended Direct	0x09	0x00 -> 0xFF (Don't Care Value; Always enter group 0x01 linking)	0x00	See Extended Enter Linking mode Info
	Response	Device's ID	Sender's ID	Ack	0x09	Same as sent		
	Sent from Device	Device's ID	0x02 0x2A 0xXX (firmware revision)	Broadcast	0x01	0x00	Same as holding down SET Button for 3 seconds	Same as holding down SET Button for 3 seconds

Extended Enter Linking mode Info									
Data 2 (1 byte)	Data 3	Data 4 (1 byte)	Data 5	Data 6	Data 7	Data 8	Data 9	...	Data 14
0x00	0x00	0x00	0x00	0x00	0x00	0x00	0x00		Checksum (0xF6, for group 1 in cmd2)

Remote Enter Unlinking Mode Command

Description: Same as holding down the SET Button for 3 seconds on the device, then pressing and holding the set button for 3 seconds. Blinks the LED red for 4 minutes or until unlinked from another device.

Example (Hex): DD EE FF AA BB CC OF OA 01 (where DD.EE.FF is the Sender's ID, AA.BB.CC is the Device's Id)

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Data 1 (1 byte)	Data 2 (1 byte)
Enter Unlinking Mode	To device	Sender's ID	Device's ID	Extended Direct	0x0A	0x00 -> 0xFF (Don't Care Value; Always enter group 0x01 linking)	0x00	See Extended Enter Unlinking mode Info
	Response	Device's ID	Sender's ID	Ack	0x0A	Same as sent		
	Sent from Device	Device's ID	0x02 0x2A 0xFF (firmware revision)	Broadcast	0x01	0x00	Same as holding down SET Button for 3 seconds	Same as holding down SET Button for 3 seconds

Extended Enter Unlinking mode Info									
Data 2 (1 byte)	Data 3	Data 4 (1 byte)	Data 5	Data 6	Data 7	Data 8	Data 9	...	Data 14
0x00	0x00	0x00	0x00	0x00	0x00	0x00	0x00		Checksum (0xF5, for group 1 in cmd2)

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Notes
Set Operating Flags	To device	Sender's ID	Device's ID	Extended Direct	0x20	Operating Flags Command	See Set Operating Flags Table below Data 14 to contain Checksum
	Response	Device's ID	Sender's ID	Ack	0x20	Same as sent	

Set Operating Flags Table	
0	Programming lock On
1	Programming lock off
2	LED on with Insteon TX
3	LED off with Insteon TX
4	Resume Dim On
5	Resume Dim Off
6	Load Sense On
7	Load Sense Off
8	Led Off
9	Led On

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Data 1 (1 byte)	Data 2 (1 byte)
Get for Group/Button	To device	Sender's ID	Device's ID	Extended Direct	0x2E	0x00	0x00	0x00
	Response	Device's ID	Sender's ID	Standard Ack	0x2E	0x00	N/A	N/A
	From device	Device's ID	Sender's ID	Extended Direct	0x2E	0x00	Same as sent	See Returned Extended Get Message Info

Returned Extended Get Message Info									
Data 2 (1 byte)	Data 3	Data 4	Data 5	Data 6	Data 7	Data 8	Data 9	Data 10	Data 14
0x01	N/A	N/A	X10 House code (0x20 = none)	X10 Unit	Ramp Rate	On-Level	LED Brightness	N/A	N/A

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Data 1 (1 byte)	Data 2 (1 byte)
Set X10 Address for Group/Button	To device	Sender's ID	Device's ID	Extended Direct	0x2E	0x00	0x00	See Set X10 Address Info
	Response	Device's ID	Sender's ID	Standard Ack	0x2E	0x00	N/A	N/A

Set X10 Address Info									
Data 2 (1 byte)	Data 3	Data 4	Data 5	Data 6	Data 7	Data 8	Data 9	Data 10	Data 14
0x04	0x00 -> 0xFF (House Code, 0x20 for none)	0x00 -> 0xFF (Unit Code)	N/A	N/A	N/A	N/A	N/A	N/A	Checksum

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Data 1 (1 byte)	Data 2 (1 byte)
Set for Ramp Rate	To device	Sender's ID	Device's ID	Extended Direct	0x2E	0x00	0x00	See Set Ramp Rate Info
	Response	Device's ID	Sender's ID	Standard Ack	0x2E	0x00	N/A	N/A

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Data 1 (1 byte)	Data 2 (1 byte)
Get Database	To device	Sender's ID	Device's ID	Extended Direct	0x2F	0x00	0x00 -> 0xFF (Don't Care Value)	See Get Database Info
	Response	Device's ID	Sender's ID	Standard Ack	0x2F	0x00	N/A	N/A
	From device	Device's ID	Sender's ID	Extended Direct	0x2F	0x00	Same as sent	See Returned Extended Get Database Info

Get Database Info									
Data 2 (1 byte)	Data 3	Data 4	Data 5	Data 6	Data 7	Data 8	Data 9	Data 10	Data 14
0x00	0x00 -> 0xFF (Hi Byte Address)	0x00 -> 0xFF (Lo Byte Address)	0x00 -> 0xFF (# of Records, 0x00 dumps all records)	N/A	N/A	N/A	N/A	N/A	N/a

Returned Extended Get Database Info (will continue to be sent until # of records is sent or until the first never been used record is sent)									
Data 2 (1 byte)	Data 3	Data 4 (1 byte)	Data 5	Data 6	Data 7	Data 8	Data 9	...	Data 14
0x01	0x00 -> 0xFF (Hi Byte Address)	0x00 -> 0xFF (Lo Byte Address)	0x00	Byte 1 of record	Byte 2 of record	Byte 3 of record	Byte 4 of record		Byte 8 of record

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Data 1 (1 byte)	Data 2 (1 byte)
Set Database	To device	Sender's ID	Device's ID	Extended Direct	0x2F	0x00	0x00 -> 0xFF (Don't Care Value)	See Set Database Info
	Response	Device's ID	Sender's ID	Standard Ack	0x2F	0x00	N/A	N/A

Set Database Info									
Data 2 (1 byte)	Data 3	Data 4 (1 byte)	Data 5	Data 6	Data 7	Data 8	Data 9	Data 13	Data 14
0x02	0x00 -> 0xFF (Hi Byte Address)	0x00 -> 0xFF (Lo Byte Address)	0x01 -> 0x08 (# of bytes to write, over 0x08 is an error and ignored)	Byte 1 of data	Byte 2 of data	Byte 3 of data	Byte 4 of data	Byte 8 of data	Checksum

Extended Command	Message Direction	From Address (3 bytes)	To Address (3 bytes)	Message type	Cmd1 (1 byte)	Cmd2 (1 byte)	Data 1 (1 byte)	Data 2 (1 byte)
Trigger Group	To device	Sender's ID	Device's ID	Extended Direct	0x30	0x00	0x00 -> 0xFF (Group/Button)	See Trigger Group Info
	Response	Device's ID	Sender's ID	Standard Ack	0x30	0x00	N/A	N/A

Trigger Group Info									
Data 2 (1 byte)	Data 3	Data 4 (1 byte)	Data 5	Data 6	Data 7	Data 8	Data 9	...	Data 13
0x00 = use local On-Level, 0x01 = use Data 3 Level (Note: The Command to the group is not parsed, so if you want the local load to go off, you must set data2 to 1 and data3 to 0)	0x00 -> 0xFF (On-Level if data2 = 0x01)	Cmd1	Cmd2	0x00 = local Ramp Rate, 0x01 = instant Ramp Rate	N/A	N/A	N/A		N/A

Checksum Information

For Set Database, Set Properties and 0x20, Data14 will contain a 2s compliment of cmd1 through 2nd to last data record in the last data record.

Example of Checksum:

01 02 03 04 05 06 1F 2F 00 01 02 0F FF 08 E2 01 08 B6 EA 00 1B 01 11
From 01.02.03 to 04.05.06
a record at 0FFF (A valid boundary)
08 bytes a record that 04.05.06 will control
Group 1 the responder is 08.B6.EA (00 1B 01 DNC)
11 is the check sum

Int	Hex	
47	2F	
0	00	
1	01	
2	02	
15	0F	
255	FF	
8	08	
226	E2	
1	01	
8	08	
182	B6	
234	EA	
0	00	
27	1B	
1	01	
1007	3EF	Sum
	10	Compliment (Last byte)
	11	Add 1